



IMPORTANT:

*Carefully unpack all parts and identify them with parts list before attempting to assemble.

*Do not tighten all screws until you have completed assembly.

1. Put 5 CASTERS (1) into the holes on 5 STAR BASE (2).
2. Insert GAS LIFT (3) to the center hole on top of 5 STAR BASE (2).
3. Insert TELESOPING COVER (4) over GAS LIFT (3).
4. Attach SEAT PLATE (5) to SEAT CUSHION (6) by inserting 4 SCREWS (9A&9B).
5. Attach both left and right ARMRESTS (7A &7B) to SEAT CUSHION (6) by inserting 6 SCREWS (9C).
6. Put BACK CUSHION (8) on SEAT CUSHION (6) by inserting 4 SCREWS (9C)
7. Insert the pre-assembled unit onto the gas lift to finish the assembly.

ATTENTION:

*Make certain all screws are fully tightened before using chair.

*Periodically (every 90 days) make sure that the screws are still fully tightened.

Parts List

1. CASTER	5
2. 5 STAR BASE	1
3. GAS LIFT	1
4. TELESOPING COVER	1
5. SEAT PLATE	1
6. SEAT CUSHION	1
7A. RIGHT ARMREST	1
7B. LEFT ARMREST	1
8. BACK CUSHION	1
9A. SCREW (Φ 1/4 X 1-1/4)	2
9B. SCREW (Φ 1/4 X 3/4)	2
9C. SCREW (Φ 5/16 X 1)	10